

Shopping List

Protective equipment:

- Safety glasses
- Nitrile gloves
- Vapour mask
- Dust mask
- Spray overalls

Paint:

- Plastic or Etch Primer if required
- Primer (+Activator)
- Colour (+Activator)
- Clear Coat (+Activator)
- Thinners

Sandpaper:

- P80
- P180
- P240
- P320
- P400/500
- P1000
- P2000
- Scotch Brite

Consumables:

- Mixing/Measuring Stick
- Masking tape
- Masking paper or plastic film
- Wax & Grease remover
- Plastic drop sheet
- Rags
- Sanding block
- Bog (+Applicator)
- Tack Cloth
- Fine cut and polish compound

AUTOMOTIVE



Safety

Wear protective gloves. Wear eye or face protection. Keep away from ignition sources such as heat/sparks/open flame. - No smoking. Do not breathe vapour or spray mist. Wash hands thoroughly after handling. Product Technical Data Sheets & Safety Data Sheets are available from Linkup Paint Supplies or at www.mypdm.nz



Recommended Gun Setup

- Fan:** Full out then half turn in
- Fluid:** 4 turns out
- Gauge:** 2 Bar (30psi)

Pro Tips

Check you have all required products before starting the job.

Sharp paint edges must be feathered back by sanding otherwise they will still be visible after the repair.

Primer will not hide deep scratches, apply body filler to repair these areas.

Practice application technique and check colour on paper before applying to your car.

If you get a run during paint application, don't worry. Let the coating dry and lightly sand the run back to a smooth finish before proceeding.

Paint mist will carry some distance, it is important to protect your vehicle and surrounding items from overspray.

The advice given in this guide is general in nature. For the best quality repair, we recommend using an authorised repairer.

Notes

Vehicle Make:
Colour Code:
Year:



Look for this sign in store to make sure you have the right product for the job

Linkup Paint Supplies
6 Killarney Lane, Frankton, Hamilton 3204
P: 07 847 0933 E: contact@linkup.co.nz